



## LED Waterproof Batten



UNIT: cd — 180 — 270 — 390  
NWB1413 57W 6500K



### TECHNICAL DETAILS

- SMD LEDs
- IP65 and IK08 ratings
- Efficacy Up to 130lm/w
- 50,000 hours of lifetime

### APPLICATIONS

Basic Lighting / Warehouse / Tunnel / Car Parks

### FEATURES

- PC housing and opal PC diffuser

### OPTIONS

- Choice of the emergency power driver supply, motion sensor and dimmable driver supply versions make to order.

Model	Power(W)	Lumens	LM/W	Size/mm	Angle	Flicker	PF	Driver
NWB1411(Single Tube)	17	2000	118	605*80*75	110°-130°	No Flicker	0.9	Separate
NWB1411(Double Tube)	22	2600	118	605*115*72	110°-130°	No Flicker	0.9	Separate
NWB1412(Single Tube)	22	2600	118	1205*82*71	110°-130°	No Flicker	0.9	Separate
NWB1412(Double Tube)	40	4800	120	1205*115*72	110°-130°	No Flicker	0.9	Separate
NWB1413(Single Tube)	36	4320	120	1505*82*71	110°-130°	No Flicker	0.9	Separate
NWB1413(Double Tube)	57	6840	120	1505*115*72	110°-130°	No Flicker	0.9	Separate